

TWINWALL SHEET **TEKPOL®/KARTONPLAST®**



КЕУРАСК

výroba a vývoj obalů – Kartonplast

TWINWALL SHEET **TEKPOL®/KARTONPLAST®**

TEKPOL®/KARTONPLAST® sheet is made of polypropylene in the form of twinwall sheet of the following parameters:

General information (sheet 2000 x 2400 or 2000 x 1200 mm)

Standard thicknesses	2 mm	2 mm	3 mm	4 mm	5 mm	6 mm	8 mm	10 mm	12 mm
Standard grammages of 1 m ²	250 g	330 g	500 g	750 g	1000 g	1200 g	1600 g	2000 g	2500 g

Technical specification

Length	300 ÷ 1000 mm ± 10 mm 1001 ÷ 2000 mm ± 20 mm 2001 ÷ 6000 mm ± 1,5%
Width	400 ÷ 2400 mm ± 5 mm
Thickness	2 ÷ 6 mm ± 0,2 mm for thickness 6 ÷ 12 mm ± 0,3 mm
Weight	± 5%
Corona treatment (optional)	38 ÷ 56 mN/m ± 4 mN/m durability min. 6 months from the date of sale provided storing in original packing
UV stability (optional)	standard durability 2 years from the date of sale at the direct exhibition in outdoor conditions for the Polish climatic zone
Printing	on request

Assortment:

- ⊗ standard colour: natural, white, black, grey
- ⊗ other dimensions, cuttings and colours on request
- ⊗ raw material: PP

Other technical abilities:

- ⊗ antistatic agent
- ⊗ UV stabilizer
- ⊗ corona treatment
- ⊗ pp conductive type with surface resistance 10⁴-10⁶Ω
- ⊗ HDPE sheets are available in thickness 4-6 mm
- ⊗ sheets' edges welding, reeling, bending line, decorative transparent sheets, silk – screen and flexographic printing
- ⊗ sheet one side laminated with functional layer: antislip, aluminium, decorative (e.g. wood imitation)
- ⊗ manufacture of packages according to Customer's individual needs

Twinwall sheet **TEKPOL®/KARTONPLAST®** is durable, moisture and mechanical shock resistant.

Application:

- ⊗ interlayers: transport of industrial goods e.g. glass-ware
- ⊗ construction/building: moisture barrier for walls and floors, door panels, construction panels
- ⊗ advertisement: signboards, billboards, bags, briefcases
- ⊗ protection: protection of palletized load edges, keeping any movable inner parts of appliances fixed e.g. in electric and gas cookers
- ⊗ insulation: heat insulation of buildings, thermal insulation of plants (refrigerating machines, dishwashers), tree casing
- ⊗ packaging: multiple usage returnable packages, pharmaceutical, automotive and food industry

More information can be obtained from the Sales Department contacting the following phone numbers:

(+420) 733 130 572
(+420) 377 222 212

KEYPACK s.r.o.
Na Roudne 80, Pilsen 301 00
Czech Republic, CZ
keypack@keypack.cz
www.keypack.cz

KEYPACK

výroba a vývoj obalů – Kartonplast

...packagings for the best!